



CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Tufting 1/10" saxony Tufté 1/10" saxony Getuftet 1/10" Saxony Getuft 1/10" saxony
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PA 6 IMPREL®
PRIMARY BACKING SUPPORT TRÄGERMATERIAL TUFTDOEK	Non woven PES Non woven PES Vlies PES Non woven PES
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Action Back
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	Ca. 1.150gr/m ²
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	Ca. 2.020gr/m ²
PILE HEIGHT EPAISSEUR DU VELOURS POLHÖHE POOLHOOGTE	Ca. 5mm
TOTAL HEIGHT EPAISSEUR TOTALE GESAMTHÖHE TOTALE DIKTE	Ca. 8mm
TUFT DENSITY NOMBRES DE POINTS NOPPENZAHL AANTAL PUNTEN	Ca. 209000/m ²
PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTE POOLDICHTHEID	Ca. 0.153g/cm ³
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 33 - LC4
UPEC	U3s P3 E1 C0 (col. 33/38 = U3 P3) Certification CSTB:11/286
CASTOR CHAIR SUITABILITY CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID	EN 985 A: intensive use
STAIR SUITABILITY ESCALIERS TREPPENEIGNUNG TRAPPENGESCHIKTHEID	EN 1963 A: intensive use

PERMANENTLY ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH	ANTISTATIC PERMANENT ANTISTATISCH	ISO 6356 < 2 kV
IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG GELUIDSISOLATIE		ISO 140-8 26 dB ΔLw
SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE		ISO 354 0.20 α _w
THERMAL RESISTANCE RÉSISTANCE THERMIQUE WÄRMEDURCHLASSWIDERSTAND WARMTEDOORLAATWEERSTAND		ISO 8302 0.17 m ² K/W
FASTNESS TO LIGHT SOLIDITÉ À LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID		ISO 105-B02 ≥ 5-6
COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHEIT WATERECHEIT		EN ISO 105-E01 ≥ 4-5
FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG		EN 13501-1 Bfl-s1 (if glued) / Cfl-s1
RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID		EN ISO 105-X12 ≥ 4
NUMBER OF COLOURS NOMBRES DE COULEURS ANZAHL FARBEN AANTAL KLEUREN		31
WIDTH LARGEUR BREITE BREEDTE		EN ISO 3018 ca. 400 cm




TUV NORD
Systeme
Vollständig geprüfter
Garnitur & Co. AG
According to TÜV NORD Standards


Suitable for
Allergic Persons
Wall to wall carpet of
allergen-tested
material
3.2-2384/05



GUT
TESTED
ENVIRONMENT - CARPETS TESTED FOR A BETTER LIVING ENVIRONMENT




QB




UPEC


moquettes touffetées et
tissées en lés
<http://evaluation.cstb.fr>



Gng Glej Rpe



EMISSIONS DANS L'AIR INTÉRIEUR
A+
A+ A B C



EAC

EN14041

CE

16


DOP: 1011#1E0ABV

REG. NR
6F7612AC
www.pro-dis.info

prominent ^{AB}




□ 70



□ 90




□ 76



□ 195



□ 72




□ 193

□ 69




□ 33



□ 27




□ 26



□ 29



□ 79



□ 191



□ 38



□ 11




□ 16



□ 18



□ 77



□ 96



□ 34



□ 54




□ 43



□ 48



□ 78



□ 197



□ 37



□ 49



□ 39



□ 47



□ 198



□ 98